

# Technical Specifications

### **Specifications**

Power Rating: 115 V, 60 Hz, 8.6 Amp Dimensions: 15 x 15 x 23 inches

(38 x 38 x 58.4 cm)

Weight: 55 pounds (25 kg)

Construction: 304-series stainless steel &

durable plastic

Spin Speed: 3450 RPM Motor: 1/3 horsepower Cycle Time: 8 seconds

Power Consumption: 1.82 watts per cycle\* Certifications: Underwriters Laboratories,

Underwriters Laboratories Canada





## **Safety Features**

Manual self-start and self-stop No exposed moving parts Built-in ground fault circuit interrupter (GFCI)

#### **Recommended Unit** and Utilities Location Diagram Centerline of $\frac{3}{8}$ inch [9.5 mm] $rac{3}{8}$ inch [9.5 mm] diameter hole used to locate the Top of Wall Sign is located 60 11 inches [27.9 cm] The upper center +/-<sup>1</sup>/<sub>16</sub> inches [152.5 cm +/hole of the Wall Mount Bracket 31 inches [8.9 cm] 3 inches [7.6 cm] 2 mm] above has to be located 4 inches [10.2 cm] floor and 38 +/- 1/16 inches [96.5 cm +/- 2 mm] [17.8 cm] centered over Suggested location for Internal Connection to Customers' Waste the (open) Lid as Suggested location 1 inch [2.5 cm] for Internal -3<sup>5</sup>/<sub>16</sub> inches [8.4 cm] Connections of

#### Installation

Wall mounted via supplied Wall Mount Bracket Direct electrical connection to a 115 V, 60 Hz, 20 Amp dedicated circuit

Water drainage to approved sanitary waste line or to floor drain

## **Operating Features**

Easy to follow instructions

Manual self-start and stop via hand pressure

on the lid

Removes approximately 95% of a swimsuit's

water in 8 seconds

Uses no heat

Model	Configuration
EC3	115 V, 60 Hz, 8.6 Amp

\*Varies based on basket load



Email: info@petrasoap.com • Web: www.petrasoap.com • Phone: 1-800-463-2516